## **Easy-Trunk<sup>®</sup> and Porta-Trunk<sup>®</sup> Fume Collectors**

Compact and portable fume collectors effectively filter smoke, dust, and fumes resulting from welding and grinding applications.



#### **Easy-Trunk Collector**

- For heavier duty or more frequent plant operations.
- Built-in pulse filter cleaning system.
- Push buttons conveniently located on front of unit and on fume hood.
- Ultra-Web® nanofiber filters provide high MERV\* 13 filtration efficiency.
- "Plug and go" operation.
- Fits easily through standard doorway.





#### **Porta-Trunk Collector**

- For light duty or infrequent plant operations.
- Static (non-pulsed) filter system.
- Operating controls conveniently located on fume hood
- Ultra-Web® nanofiber filters provide high MERV\* 13 filtration efficiency.
- "Plug and go" operation.
- Fits easily through standard doorway.

#### **Easy-Trunk and Porta-Trunk Collectors**

#### **Dimensions & Specifications**





**Easy-Trunk** 

**Porta-Trunk** 

	Nominal		Dimensions (inches)			Shipping	
Model	Airflow** (cfm)	Motor (hp)	A	В	С	Weight (lbs)	Sound Level dB(A)†
Easy-Trunk	750	1.5	28.0	40.9	38.6	400	70
Porta-Trunk	780	1.5	27.5	40.3	35.4	340	75

#### **Standard Features**

- Ultra-Web® FR filter cartridges
- 1.5 hp TEFC motor
- 115/60/1 voltage
- Extraction arm: 6 in. x 6.5 ft.
- · Hood-mounted light with switch
- · Fully assembled and wired
- 10-year warranty
- \* The Minimum Efficiency Reporting Value (MERV) of this filter cartridge has been determined through independent laboratory testing using ASHRAE 52.2 (1999) test standards. The MERV rating was determined at a face velocity of 118 feet per minute and loading up to four inches water gauge. Actual efficiency of any filter cartridge will vary according to the specific application parameters. Dust concentration, airflow, particle characteristics, and pulse cleaning methods all affect filtration efficiency.


#### **Equipment Options**

• Extraction arm: 6 in. x 10 ft.

- \*\* Based on clean filters.
- † Sound level per ANSI S12.34.1988. The actual measured sound level will vary, depending on background noise and room conditions.



Donaldson Company, Inc. Industrial Air Filtration P.O. Box 1299 Minneapolis, MN 55440 Tel 800-365-1331(USA) Tel 800-343-3639 (within Mexico) dustmktg@mail.donaldson.com www.donaldsontorit.com



#### Visit us at www.donaldsondynamic.com

Information in this document is subject to change without notice. U.S. Patent 4,860,644

© 1998 Donaldson Co., Inc. Printed in U.S.A. on recycled paper Data Sheet EZ-PT (01/07)



Visit us online at DustCollectionPros.com

# Our Business is Improving Your Workplace Air Quality.



ince 1995, Environmental Solutions has been helping businesses, like yours, improve their workplace air quality. As an authorized service center for Donaldson Torit, we offer you a one-stop shop for equipment, service, engineering and installation of the industry's leading air pollution control systems.

Whether your company requires the removal of oil mist, welding fumes, machining or woodworking dust, graphite, or correction of any other type of air quality problem; we can expertly engineer and install a quality Donaldson Torit solution to meet your unique needs. No system is too big or too small.

### **TOLL FREE 1-866-438-7891**



12427 Fire Island Drive Loves Park, IL 61111 Phone: (847) 370-9304

Environmental Solutions is also your source for discount pricing on genuine Donaldson Torit Replacement Filters!